AMENDMENTS TO THE CLAIMS:

Upon entry of this Response by the Examiner, this listing of claims will replace all prior versions and listings of claims in the application:


1. (**Currently Amended**) A wind turbine gear additive concentrate, comprising:

a) an extreme pressure compound comprising a sulfur-containing compound;

b) load carrying capacity enhancing combination comprising


(i) a hydrocarbylamine compound selected from the group consisting of N-oleyl-trimethylene diamine, N-tallow-trimethylene diamine, N-coco-trimethylene diamine, and combinations thereof, and

(ii) an alkylphosphoro(mono)thioate compound represented by the formula:



where each of R^1, R^2, and R^3 is, independently, an unsubstituted alkyl group or a hydrogen atom, and where at least one of R^1, R^2, and R^3 is an unsubstituted alkyl group, and where each of X^1, X^2, and X^3 represents an oxygen atom;

c) a long chain alkyl phosphonate friction modifying compound represented by the formula:



wherein R^a is an alkyl group ~~comprising~~ having from about 12 to about 18 carbon atoms and R^b and R^c each independently comprise from about 1 to about 4 carbon atoms; and

d) a diluent oil,

wherein any of compounds a), b)(i), b)(ii), and c) can be the same or different compounds.

2. (**Cancelled**)

3. (**Cancelled**)

4. (**Cancelled**)

5. (**Currently Amended**) The additive concentrate according to claim [[4]] 1, wherein at least one of R^1, R^2, and R^3 is an unsubstituted aliphatic alkyl group of 3 to 20 carbon atoms.

6. (**Currently Amended**) The additive concentrate according to claim 1, comprising about 20 to about 60 wt. % extreme pressure compound comprising a sulfur-containing compound; about 10 to about 30 wt. % hydrocarbylamine compound; about 10 to about 30 wt. % alkylphosphoro(mono)thioate compound; about 10 to about 30 wt. % friction modifying compound; and ~~a minor amount of~~ diluent oil.

7. (**Previously Presented**) The additive concentrate according to claim 1, wherein the extreme-pressure agent comprises a metal-free sulfur-containing extreme-pressure agent selected from the group consisting of sulfurized olefin and polysulfide

composed of one or more groups represented by the formula R_a--S_x--R_b where R_a and R_b are hydrocarbyl groups each of which contains 3 to 18 carbon atoms and x is in the range of from 2 to 8.


8. (**Currently Amended**) A wind turbine gear composition, comprising:

a) an extreme pressure compound comprising a sulfur-containing compound;

b) load carrying capacity enhancing combination comprising


(i) a hydrocarbylamine compound selected from the group consisting of N-oleyl-trimethylene diamine, N-tallow-trimethylene diamine, N-coco-trimethylene diamine, and combinations thereof, and

(ii) an alkylphosphoro(mono)thioate compound represented by the formula:



where each of R^1, R^2, and R^3 is, independently, an unsubstituted alkyl group or a hydrogen atom, and where at least one of R^1, R^2, and R^3 is an unsubstituted alkyl group, and where each of X^1, X^2, and X^3 represents an oxygen atom;

c) a long chain alkyl phosphonate friction modifying compound represented by the formula:



wherein R^a is an alkyl group ~~comprising~~ having from about 12 to about 18 carbon atoms and R^b and R^c each independently comprise from about 1 to about 4 carbon atoms; and

d) a base oil,

wherein any of compounds a), b)(i), b)(ii), and c) can be the same or different compounds with the proviso that b)(i) and b)(ii) are different.

9. (**Cancelled**)

10. (**Cancelled**)

11. (**Cancelled**)

12. (**Currently Amended**) The composition according to claim [[11]] 8, wherein at least one of R^1, R^2, and R^3 is an unsubstituted aliphatic alkyl group of 3 to 20 carbon atoms.

13. (**Previously Presented**) A composition according to claim 8, comprising about 0.5 to about 2.5 wt. % extreme pressure compound comprising a sulfur-containing compound; about 0.1 to about 1.0 wt. % hydrocarbylamine compound; about 0.1 to about 1.0 wt. % alkylphosphoro(mono)thioate compound; about 0.1 to about 1.0 wt. % friction modifying compound; and ~~a major amount of~~ about 90 to about 99 wt.% base oil.

14. (**Previously Presented**) The composition according to claim 8, wherein the extreme-pressure agent comprises a metal-free sulfur-containing extreme-pressure


agent selected from the group consisting of sulfurized olefin and polysulfide composed of one or more groups represented by the formula R_a--S_x--R_b where R_a and R_b are hydrocarbyl groups each of which contains 3 to 18 carbon atoms and x is in the range of from 2 to 8.

15. (**Previously Presented**) The composition according to claim 8, wherein the composition has a kinematic viscosity of at least 12 cSt at 100°C.

16. (**Original**) The composition according to claim 8, wherein the base oil has a viscosity in the range of SAE 50 to SAE 250.


17. (**Original**) The composition according to claim 8, wherein the base oil has a viscosity in the range of SAE 70W to SAE 140.

18. (**Currently Amended**) A method of manufacturing a composition suitable for use in a wind turbine gear assembly comprising blending a base oil; an extreme pressure compound comprising a sulfur-containing compound; a hydrocarbylamine compound selected from the group consisting of N-oleyl-trimethylene diamine, N-tallow-trimethylene diamine, N-coco-trimethylene diamine, and combinations thereof; an alkylphosphoro(mono)thioate compound represented by the formula:



where each of R^1, R^2, and R^3 is, independently, an unsubstituted alkyl group or a hydrogen atom, and where at least one of R^1, R^2, and R^3 is an unsubstituted alkyl

group, and where each of X^1, X^2, and X^3 represents an oxygen atom; and a long chain alkyl phosphonate friction modifying compound represented by the formula:



wherein R^a is an alkyl group ~~comprising~~ having from about 12 to about 18 carbon atoms and R^b and R^c each independently comprise from about 1 to about 4 carbon atoms, and wherein the composition demonstrates improved load carrying capacity as compared to a composition devoid of the hydrocarbylamine compound and alkylphosphoro(mono)thioate compound.

19. (**Original**) A method of lubricating a gear comprising using as the lubricant for said gear a gear oil composition according to claim 8.

20. (**Original**) A lubed gear-box comprising a gear within the gear box, in which the gear is lubricated according to the method of claim 19.

21. (**Original**) A method of lubricating a wind turbine gear assembly comprising using as the lubricant for said gear assembly a composition according to claim 8.

22. (**Original**) A wind turbine gear assembly lubricated with a composition according to claim 8.